

Version Wall - 55 cm - Satin Black - 800 m3/h

Collection Design

TECHNICAL FEATURES

Materials/Finishes Painted black steel

Materials/Finishes Black glass satin finishing

Features Opening frontal

Control Electronic control

Function Extracting/Filtering

Chimney Possible to duct wall mounted from rear
Optional chimney

Lighting Dimmable lighting
Dynamic Light (2700K - 5600K)
LED 2x1,2 W - 2700 K / 5600 K

Filters Metallic grease filter, removable and washable
Combined Carbon.Zeo Microtech regenerable filter (optional)
Charcoal filter

Dimensions 55 cm

Minimum Electric hob distance 52 cm

Minimum Gas hob distance 52 cm

Notes Dynamic and dimmable Led light from 03.04.24

CONNECTION AND CONSUMPTION FUNCTIONS

Maximum consumption 280 W

Voltage/Frequency 220-240V 50-60Hz

Plug Shuko

MOTOR

Motor 800 m³/h

Maximum capacity 500 m³/h I.E.C.61591

Maximum sound level 58 dB (A)re1pW I.E.C. 60704-2-13

Energy class A

WEIGHTS AND VOLUMES

Gross weight 22 kg


Net weight 17 kg

Volume 0.25 m³

Packaging dimensions L 775 x H 452 x P 705 mm



Photograph is for information purposes only. May not correspond to the selected version




Optional accessories


Code	Description
KACL.958#NF	External Carbon.Zeo filter unit for sloped hoods (Black)
KCQAN.00#I	Chimney - Inox
KCQAN.00#N	Chimney - Black
KACL.1059	Conveyer for air outlet (Ø150)
FDS 100 Schabus	
KITRROND	

ENGINE SPECIFICATIONS

Motor speed	1	2	3	4
Noise dB(A) re1pW I.E.C. 60704-2-13	46	53	58	66
Capacity	295	390	500	750
Maximum pressure (Pa)	390	440	490	510
Motor power (W)	130	150	178	224
Air outlet	150	150	150	150

FLOW RATE / PRESSURE





PF		
S		
M	Wall - 55 cm - Satin Black - 800 m3/h	
AEC	57.70	kWh/a
EEC	A	
FDE	29.40	
FDEC	A	
LE	21.60	
LEC	B	
GFE	82	
GFEC	C	
Qmin	295	m³ /h
Qmax	500	m³ /h
Qboost	750	m³ /h
SPEmin	46	dBa
SPEmax	58	dBa
SPEboost	66	dBa
PO	0	W
PS	0.48	W
PI		
F	0.90	
EEL	53.20	
Qbep	430	m³ /h
Pbep	404	Pa
Qboost	750	m³ /h
Wbep	164	W
WL	5.30	W
Emiddle	114	lux
Lwa-SPEmax	58	dBa

PF_Scheda prodotto conforme a 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / P0_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps).

PI_Additional information according to 66/2014 Calculation methods: EN 61591:2020 F_Time increase factor / EEL_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximum air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.